

L & M SUPPLY CO., INC.

P.O. Box 640
1800 Springhead Ch. Rd.
Willacoochee, Ga. 31650

912-534-6071
800-948-7870
912-534-6254(fax)

Subject: L & M Filter Bags / Dewatering Bags

This letter certifies **L & M Filter Bags / Dewatering Bags**, manufactured by L&M Supply Co., are made with 8oz Non Woven Geotextile Fabric. **L & M Filter Bags / Dewatering Bags** are inert to biological degradation and resists naturally encountered chemicals, alkalis, and acids. The stitching is a Durable, Double Thread Chain Stitch. **Standard Sizes:** 6' X 6', 10' X 15' and 15' X 15'. Custom Sizes are available. The average laboratory test values are as follows:

PROPERTY	TEST METHOD	UNIT	ROLL VALUE MARV
Tensile Strength	ASTM D 4632	Lbs	205
Elongation	ASTM D 4632	%	50
Mullen Burst	ASTM D 3786	PSI	380
Trapezoidal Tear	ASTM D 4533	Lbs	80
Puncture Strength	ASTM D 4833	Lbs	130
AOS	ASTM D 4751	Sieve	80
Permittivity	ASTM D 4491	Sec-1	1.2
Permeability	ASTM D 4491	Cm/sec	0.22
Water Flow Rate	ASTM D 4491	Gpm/ft	95
UV Resistance	ASTM D 4355	%	70/500

Unless otherwise noted, this certification is based on testing conducted by our Quality Assurance & Quality Control testing laboratories at the time of manufacturing. L & M Supply Co., Inc. issued this letter of certification to indicate our commitment to providing our customers with a quality product which will meet or exceed the minimum average roll values in accordance with the applicable American Society for Testing and Materials (ASTM) test method.

Respectfully,

Quincy McMillan