



P.O. Box 640
1800 Springhead Ch. Rd.
Willacoochee, Ga. 31650

912-534-6071
800-948-7870
912-534-6254(fax)

Subject: LM 1000

This letter certifies that our 10oz. Non-woven filter fabric, manufactured by L&M Supply Co., classified as L&M 1000, meets the requirements for non-woven geotextile fabric. The average laboratory test values are as follows:

PROPERTY	TEST METHOD	UNIT	ROLL VALUE
Tensile Strength	ASTM D 4632	Lbs	250
Elongation	ASTM D 4632	%	50
Trapezoidal Tear	ASTM D 4533	Lbs	100
CBR Puncture Strength	ASTM D 6241	Lbs	700
AOS	ASTM D 4751	Sieve	100
Permittivity	ASTM D 4491	Sec-1	1.2
Water Flow Rate	ASTM D 4491	Gpm/ft	80
UV Resistance	ASTM D 4355	%	70/500

Unless otherwise noted, this certification is based on testing conducted by our Quality Assurance & Quality Control testing laboratories at the time of manufacturing. L & M Supply Co., Inc. issued this letter of certification to indicate our commitment to providing our customers with a quality product which will meet or exceed the minimum average roll values in accordance with the applicable American Society for Testing and Materials (ASTM) test method.

Respectfully,

Quincy McMillan