



P.O. Box 640  
1800 Springhead Ch. Rd.  
Willacoochee, Ga. 31650

912-534-6071  
800-948-7870  
912-534-6254(fax)

Subject: LM 1200

This letter certifies that our 12oz. Non-woven filter fabric, manufactured by L&M Supply Co., classified as **LM 1200**, meets the requirements for non-woven geotextile fabric. The average laboratory test values are as follows:

PROPERTY	TEST METHOD	UNIT	ROLL VALUE
Mass per Unit Area	ASTM D 5261	Oz/yd <sup>2</sup>	12.0
Tensile Strength	ASTM D 4632	Lbs	300
Elongation	ASTM D 4632	%	50
Trapezoidal Tear	ASTM D 4533	Lbs	115
CBR Puncture Strength	ASTM D 6241	Lbs	850
AOS	ASTM D 4751	Sieve	100
Permittivity	ASTM D 4491	Sec-1	1.0
Water Flow Rate	ASTM D 4491	Gpm/ft	75
UV Resistance	ASTM D 4355	%	70/500

Unless otherwise noted, this certification is based on testing conducted by our Quality Assurance & Quality Control testing laboratories at the time of manufacturing. L & M Supply Co., Inc. issued this letter of certification to indicate our commitment to providing our customers with a quality product which will meet or exceed the minimum average roll values in accordance with the applicable American Society for Testing and Materials ( ASTM ) test method.

Respectfully,

Quincy McMillan