

L & M SUPPLY CO., INC.

P.O. Box 640

Willacoochee, GA 31650

Phone: 800-948-7870 Fax: 912-534-6254

Rolled Jute Mesh Specifications

Subject: Certification Rolled Jute Mesh

Description

Jute erosion control mat is woven from spun jute yarns. The mat contains about 65% open area. This completely biodegradable blanket is the solution to environmentally sensitive general erosion control applications requiring up to 6—9 months of functional life.

This letter certifies that our L&M Jute Mesh meets and/or exceeds the specifications listed below. The average laboratory test values for the L&M Jute Mesh are as follows:

Specifications

Material	Jute Mesh
Roll size	4' x 225' (width x length) (1.22 m x 68.6 m)
Roll Area	100 SY (83.3 sq.m.)
Open Area	60-65%
Water Absorption	>450% of fabric weight
Thickness	0.25 inch (6 mm)
Recommended shear stress	0.45 lbs./sq.ft. (22 N/sq.m)
Recommended flow	6 fps (1.8 m/s)
Recommended slope	3:1
Coverage	100 Square Yards/roll
Roll weight	90 Lbs (+/- 5%) 14.7 oz/SY (490 g/m ²)
Quantity per Pallet	9 and 12
Country origin	India

Unless otherwise noted, this certification is based on testing conducted by an independent testing laboratory. These test results are no more than one year old when presented to the authorizing agent. L & M Supply Co., Inc. issued this letter of certification to indicate our commitment to providing our customers with a quality product which will meet or exceed the minimum average roll values in accordance with the applicable American Society for Testing and Materials (ASTM) test method.

Respectfully,

Quincy McMillan
L&M Supply Co., Inc.